
Article code: **4248L-30154**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale

CRISTALY®**handmade in Italy**IP20
IP44C.C.
[m.A.]**Light source / Sorgente luminosa**

| | |
|-----------------------------------|--------|
| Type/Tipo | LED |
| CCT | 3000K |
| Light Source Flux/Flusso Sorgente | 650lm |
| Power/Potenza | 6,5W |
| CRI | CRI 90 |

Installation / Installazione

| | |
|------------------------------------|---|
| Type/Tipologia | CEILING RECESSED LIGHTING/ INCASSO A PLAFONE |
| Weight/Peso | 0,5Kg |
| Insulation class/Classe isolamento | III |
| IP | IP20/IP44 |

Accessories & Variants / Accessori & Varianti

All accessories and variants are available on 9010.it.
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Finishes & Colours / Finiture & Colori



CRISTALY® Paintable

Power Supply / Alimentazione

| | |
|------------------------------------|--|
| Constant Current/Corrente Costante | 350mA |
| Dimmability/Dimmerazione | AMPLITUDE, PWM (With dimmable driver/Con driver dimmerabile) |

See compatible drivers on 9010.it. Multiple modules require a series connection/Vedere
driver compatibili su 9010.it. Collegamento moduli multipli in serie

The driver must be placed in a remote box. For suggested cable length and size refer to the
driver specifications/Il driver deve essere riposto in remoto. Per la lunghezza e dimensione
cavi consigliata fare riferimento alle specifiche del driver.

Check it on 9010.it

