
Article code: **4248L-27154**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale

**CRISTALY®****handmade in Italy**IP20  
IP44C.C.  
[m.A.]**Light source / Sorgente luminosa**

Type/Tipo	LED
CCT	2700K
Light Source Flux/Flusso Sorgente	620lm
Power/Potenza	6,5W
CRI	CRI 90

**Installation / Installazione**

Type/Tipologia	CEILING RECESSED LIGHTING/ INCASSO A PLAFONE
Weight/Peso	0,5Kg
Insulation class/Classe isolamento	III
IP	IP20/IP44

**Accessories & Variants / Accessori & Varianti**

All accessories and variants are available on 9010.it.  
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Finishes &amp; Colours / Finiture &amp; Colori



CRISTALY® Paintable

**Power Supply / Alimentazione**

Constant Current/Corrente Costante	350mA
Dimmability/Dimmerazione	AMPLITUDE, PWM (With dimmable driver/Con driver dimmerabile)

See compatible drivers on 9010.it. Multiple modules require a series connection/Vedere  
driver compatibili su 9010.it. Collegamento moduli multipli in serie

The driver must be placed in a remote box. For suggested cable length and size refer to the  
driver specifications/Il driver deve essere riposto in remoto. Per la lunghezza e dimensione  
cavi consigliata fare riferimento alle specifiche del driver.

Check it on 9010.it

