
Article code: **4248L-30150**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale

CRISTALY®**handmade in Italy**IP20
IP44C.C.
[m.A.]**Light source / Sorgente luminosa**

Type/Tipo	LED
CCT	3000K
Light Source Flux/Flusso Sorgente	450lm
Power/Potenza	4W
CRI	CRI 90

Installation / Installazione

Type/Tipologia	CEILING RECESSED LIGHTING/ INCASSO A PLAFONE
Weight/Peso	0,5Kg
Insulation class/Classe isolamento	III
IP	IP20/IP44

Accessories & Variants / Accessori & Varianti

All accessories and variants are available on 9010.it.
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Finishes & Colours / Finiture & Colori

CRISTALY® Paintable

Power Supply / Alimentazione

Constant Current/Corrente Costante	200mA
Dimmability/Dimmerazione	AMPLITUDE, PWM (With dimmable driver/Con driver dimmerabile)

See compatible drivers on 9010.it. Multiple modules require a series connection/Vedere
driver compatibili su 9010.it. Collegamento moduli multipli in serie

The driver must be placed in a remote box. For suggested cable length and size refer to the
driver specifications/Il driver deve essere riposto in remoto. Per la lunghezza e dimensione
cavi consigliata fare riferimento alle specifiche del driver.

Check it on 9010.it

