



FUEGO



FUEGO il nuovo termoventilatore di JOHNSON con resistenza in ceramica a basso consumo.

Grazie ai suoi 2000 W riscalda ambienti abbastanza ampi, ideale per camere, bagni e uffici.

È integra di maglia per il trasporto, ha l'oscillazione automatica selezionabile, 2 temperature con termostato regolabile tiepido e caldo più la ventilazione.

Ha una spia luminosa che ti consente di capire quando il dispositivo è acceso, il filtro posteriore removibile e lavabile per una facile pulizia e ha un sistema di sicurezza auto spegnimento in caso di ribaltamento.

FUEGO puoi posizionarlo in qualunque luogo tu voglia grazie al suo design moderno e compatto.



FUEGO the new JOHNSON fan heater with low consumption ceramic resistance.

Thanks to its 2000 W it heats quite large rooms, ideal for bedrooms, bathrooms and offices.

It is complete with mesh for transport, has selectable automatic oscillation, 2 temperatures with adjustable warm and warm thermostat plus ventilation.

It has an indicator light that allows you to understand when the device is on, the removable and washable rear filter for easy cleaning and has an auto shut-off safety system in case of rollover.

FUEGO you can place it wherever you want thanks to its modern and compact design.



GIFT BOX		MASTER CARTON			PALLET		CONTAINER		
Size (mm)	Kg	Size (mm)	Pcs	Kg	Pcs	20	40	40HQ	
220 x 165 x 435	2.5	440 X 360 X 455	4	10.9	96	1552	3104	3720	

FUEGO

FAMILY	HEATING
CODE	FUE
COD. EAN	8008523012861
COD. ITF	18008523012868

CARATTERISTICHE	FEATURES
-----------------	----------

Potenza 1200-2000 W
 Resistenze in ceramica
 Basso consumo energetico
 Oscillazione automatica selezionabile
 2 livelli di potenza selezionabili
 Ventilazione
 Aria tiepida: 1200 W
 Aria calda: 2000 W
 Termostato regolabile
 Spia luminosa
 Maniglia integrata
 Sistema di sicurezza auto spegnimento in caso di ribaltamento dell'apparecchio
 Sistema di sicurezza anti surriscaldamento
 Filtro posteriore removibile e lavabile
 Colore: Bianco/Grigio
 Alimentazione 220 - 240V~ 50 Hz

Power 1200-2000 W
 Ceramic resistors
 Low energy consumption
 Selectable automatic swing
 2 selectable power levels
 Ventilation
 Warm air: 1200 W
 Hot air: 2000 W
 Adjustable thermostat
 Warning light
 Integrated handle
 Auto shut-off safety system in case of overturning of the device
 Overheating safety system
 Removable and washable rear filter
 Color: White / Gray
 Power supply 220 - 240V ~ 50 Hz

Dimensioni prodotto: 195 x 145 x 420 mm
 Dimensioni imballo: 220 x 165 x 435 mm
 Peso imballo + prodotto: 2.5 Kg
 Pezzi per master: 4 pz
 Dimensioni master: 440 x 360 x 455 mm
 Peso master: 10.9 Kg
 Pezzi per pallet: 96 pz
 Colli per strato: 6
 Strati: 4
 Altezza pallet: 195 cm
 Peso pallet: 290 Kg
 Container 20: 1552 pz
 Container 40: 3104 pz
 Container 40HQ: 3720 pz
 Codice certificazione: NSBK-200SK35

Product dimensions: 195 x 145 x 420 mm
 Package dimensions: 220 x 165 x 435 mm
 Packaging weight + product: 2.5 Kg
 Master pieces: 4 pcs
 Master size: 440 x 360 x 455 mm
 Master Weight: 10.9 Kg
 Pieces for pallet: 96 pcs
 Master for layer: 6
 Layers: 4
 Height pallet: 195 cm
 Weight pallet: 290 Kg
 Container 20: 1552 pcs
 Container 40: 3104 pcs
 Container 40HQ: 3720 pcs
 Certification Code: NSBK-200SK35

