
Article code: **4248A-4000**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale **CRISTALY®****handmade in Italy**IP20
IP44C.V.
[V]**Light source / Sorgente luminosa**

Type/Tipo	LED
CCT	4000K
Light Source Flux/Flusso Sorgente	210lm
Power/Potenza	2W
CRI	CRI 90

Installation / Installazione

Type/Tipologia	CEILING RECESSED LIGHTING/ INCASSO A PLAFONE
Weight/Peso	0,4Kg
Insulation class/Classe isolamento	III
IP	IP20/IP44

Accessories & Variants / Accessori & Varianti

All accessories and variants are available on 9010.it.
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Finishes & Colours / Finiture & Colori



CRISTALY® Paintable

Power Supply / Alimentazione

Tensione Costante/Costant Voltage	24Vdc
Dimmability/Dimmerazione	PWM (With dimmable driver/ Con driver dimmerabile)

See compatible drivers on 9010.it. Multiple modules require a parallel connection/Vedere driver compatibili su 9010.it. Collegamento moduli multipli in parallelo

The driver must be placed in a remote box. For suggested cable length and size refer to the driver specifications/Il driver deve essere riposto in remoto. Per la lunghezza e dimensione cavi consigliata fare riferimento alle specifiche del driver.

Check it on 9010.it

