
Article code: **4249L-27151**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale

**CRISTALY®****handmade in Italy**IP20  
IP44C.C.  
[m.A.]

Finishes &amp; Colours / Finiture &amp; Colori



CRISTALY® Paintable

**Light source / Sorgente luminosa**

|                                   |        |
|-----------------------------------|--------|
| Type/Tipo                         | LED    |
| CCT                               | 2700K  |
| Light Source Flux/Flusso Sorgente | 620lm  |
| Power/Potenza                     | 6,5W   |
| CRI                               | CRI 90 |

**Power Supply / Alimentazione**

|                                    |  |
|------------------------------------|--|
| Constant Current/Corrente Costante | 350mA  |
| Dimmability/Dimmerazione           | AMPLITUDE, PWM (With dimmable driver/Con driver dimmerabile) |

See compatible drivers on 9010.it. Multiple modules require a series connection/Vedere driver compatibili su 9010.it. Collegamento moduli multipli in serie

The driver must be placed in a remote box. For suggested cable length and size refer to the driver specifications/Il driver deve essere riposto in remoto. Per la lunghezza e dimensione cavi consigliata fare riferimento alle specifiche del driver.

**Installation / Installazione**

|                                    |   |
|------------------------------------|---|
| Type/Tipologia                     | CEILING RECESSED LIGHTING/<br>INCASSO A PLAFONE |
| Weight/Peso                        | 0,5Kg   |
| Insulation class/Classe isolamento | III   |
| IP                                 | IP20/IP44                                       |

**Accessories & Variants / Accessori & Varianti**

All accessories and variants are available on 9010.it.  
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Check it on 9010.it

