


Article code: **4249L-30153**

CEILING RECESSED LIGHTING/INCASSO A PLAFONE

Material / Materiale **CRISTALY®**



handmade in Italy



IP20  
IP44



C.C.  
[m.A.]



#### Light source / Sorgente luminosa

Type/Tipo	LED
CCT	3000K
Light Source Flux/Flusso Sorgente	450lm
Power/Potenza	4W
CRI	CRI 90

#### Installation / Installazione

Type/Tipologia	CEILING RECESSED LIGHTING/ INCASSO A PLAFONE
Weight/Peso	0,5Kg
Insulation class/Classe isolamento	III
IP	IP20/IP44

#### Accessories & Variants / Accessori & Varianti

All accessories and variants are available on 9010.it.  
Tutti gli accessori e le varianti sono disponibili su 9010.it.

Finishes & Colours / Finiture & Colori



CRISTALY® Paintable

#### Power Supply / Alimentazione

Constant Current/Corrente Costante	200mA
Dimmability/Dimmerazione	AMPLITUDE, PWM (With dimmable driver/Con driver dimmerabile)

See compatible drivers on 9010.it. Multiple modules require a series connection/Vedere  
driver compatibili su 9010.it. Collegamento moduli multipli in serie

The driver must be placed in a remote box. For suggested cable length and size refer to the  
driver specifications/Il driver deve essere riposto in remoto. Per la lunghezza e dimensione  
cavi consigliata fare riferimento alle specifiche del driver.

Check it on 9010.it

