


## SylMirror Slim/Flute

SYLMIRROR LED SLIM IP44 NW  
0043213



### Product features

- LED mirror/cabinet light with 8W total power consumption, 560 lumen, 110° beam angle, IP44, IK03, CRI 80, 4000K colour temperature, 400 mm length, 2 year warranty. Slim shape.



### NOTES

undefined

### PRODUCT OVERVIEW

Product name	SYLMIRROR LED SLIM IP44 NW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
Fixture rating	Enclosed
General application	Residential & Consumer
ETIM Class	EC002892
E-number FI	4170555
E-number SE	7505161
Warranty	2 years
Fixture luminous flux (lm)	560
Luminaire efficacy (lm/W)	70
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Total power consumption (W)	8
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Housing colour	Chrome
IP rating	IP44
IK rating	IK03
Product EAN number	5410288432137

## SylMirror Slim/Flute

SYLMIRROR LED SLIM IP44 NW  
0043213

### DATA TABLE

#### General data

Product name	SYLMIRROR LED SLIM IP44 NW
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Wall surface mounted
Fixture rating	Enclosed
General application	Residential & Consumer
Operating temperature range (°C)	-10°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
E-number FI	4170555
E-number SE	7505161
Warranty	2 years

#### Optical data

Fixture luminous flux (lm)	560
Luminaire efficacy (lm/W)	70
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Distribution type	Symmetric
Photobiological Risk Group	RG0

#### Electrical data

Total power consumption (W)	8
Mains voltage (V)	220-240V
Lamp power factor	0.5
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	100
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	60
Inrush Current (A)	2
Inrush Duration (µs)	50
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz

## SylMirror Slim/Flute

SYLMIRROR LED SLIM IP44 NW  
0043213

Max. Luminaires per 10A C Breaker	100
Max. Luminaires per 16A C Breaker	200
Max. Luminaires per 16A B Breaker	200

### Lifetime data

Lifespan L70 B50	25000
------------------	-------

### Physical data

Housing colour	Chrome
IP rating	IP44
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	400
Nominal Product Width (mm)	120
Nominal Product Height (mm)	45
Weight (kg)	0.206


### Packaging

Single packaging type	Carton
Product EAN number	5410288432137
Packaging single length / height (cm)	41.0
Packaging single width (cm)	13.2
Packaging single depth (cm)	5.5
DUN14 (outer)	15410288432134
Units per outer package	6
Packaging outer length / height (cm)	43.0
Packaging outer width (cm)	42.0
Packaging outer depth (cm)	13.5

### Safety data

Optimal operating condition (°C)	-10-45
----------------------------------	--------

## PHOTOMETRY



SylMirror Slim/Flute  
*SYLMIRROR LED SLIM IP44 NW*  
0043213

---

## TECHNICAL DRAWINGS

---

