

Start Waterproof START WATERPROOF 1200 HOUSING 1X 0047922



Caratteristiche prodotto

- Luminaire, polycarbonate housing Single version, 1200mm Protection type IP65 Luminous flux and light colour vary depending on LED tubes used Easy to install with stainless steel fixing brackets included for ceiling mounting Ideal for any industrial facilities, garages, car parks, workshops.



PANORAMICA DEL PRODOTTO

Nome prodotto	START WATERPROOF 1200 HOUSING 1X
Tecnologia	LED
Cap/Base	G13
Housing	PC Polycarbonate
Montaggio	Ceiling surface mounting
Fixture rating	Chiuso
General application	Logistics & Industry
ETIM Class	EC002892
E-number Finlandia	4309056
Garanzia	3 years
L.O.R. (%)	75
Lampada inclusa	Fixture without Lightsource
Electrical protection	Classe I
Colore corpo lampada	Grigio
IP rating	IP65
IK rating	IK08
Product EAN number	5410288479224

TABELLA DATI

Dati generali

Nome prodotto	START WATERPROOF 1200 HOUSING 1X
Tecnologia	LED
Cap/Base	G13
Housing	PC Polycarbonate
Montaggio	Ceiling surface mounting
Fixture rating	Chiuso
General application	Logistics & Industry
ETIM Class	EC002892
E-number Finlandia	4309056
Garanzia	3 years

Dati ottici

L.O.R. (%)	75
------------	----

Start Waterproof START WATERPROOF 1200 HOUSING 1X 0047922

Dati elettrici

Lampada inclusa	Fixture without Lightsource
Electrical protection	Classe I
Glow Wire Test (°C)	650

Dati dimensionali

Colore corpo lampada	Grigio
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Lunghezza nominale del prodotto (mm)	1260
Larghezza nominale prodotto (mm)	69
Nominal Product Height (mm)	78
Peso (Kg)	0.81

Dati di imballo

Tipologia imballo singolo	Carton
Product EAN number	5410288479224
Lunghezza imballo singolo (mm)	128.0
Larghezza imballo singolo (cm)	6.9
Packaging single depth (cm)	5.2
DUN14 (outer)	15410288479221
Quantità per imballo esterno	1
Packaging outer length / height (cm)	128.0
Packaging outer width (cm)	6.9
Packaging outer depth (cm)	5.2

DISEGNI TECNICI

