


**YUMA10NK**  
**Solar floodlight**

YUMA10NK

10 W - 1100lm - 3000-4000-6000K



REGOLABILE / ADJUSTABLE



DIMENSIONS	A	B	C
1	215	37	310

GENERAL INFORMATIONS	
Code	YUMA10NK
Ean	8031453030919
Family	YUMA10NK
Technology	LED
Body material	ABS
Diffuser / lens material	PC
Operating temperature (° C)	-15 - +40
Years warranty	2
LIGHTING DATA	
Light colour	CCT
CCT (K)	3000-4000-6000
Luminous flux (lm)	1100
Beam (°)	120
TECHNICAL FEATURES	
Power (W)	10
Supply voltage (V) / Max (V)	3,7 / 3,7
Power factor	>0,50
Dimmer compatibility	NO
Nominal life (h)	35000
Impact resistance (IK)	8
PACKAGING	
Packaging	BOX
Pack	8 / 8

## YUMA10NK Solar floodlight

### YUMA10NK

10W - 1100lm - 3000-4000-6000K

- Floodlight with dusk sensor and PIR presence detector
- Easy to install: does not require connection to mains energy
- Lithium ion battery 3.7V-2x3300mAh, 24.42Wh
- Material ABS + PC anti UV, self-extinguishing
- Selectable CCT

#### OPERATION

**ON/OFF KEY (1):** Press the button once, to turn on the projector. Press it again to change the color of the light. In this mode, the appliance will remain on at 30% until the battery runs out or the sun rises. Press and hold more than 3 sec to turn off the appliance.

**SENSOR MODE KEY (2):** In this mode the projector will turn on, when motion is detected, at 100% light output. If the ambient light detected through the panel is below 40lux. If no motion is detected for 30 seconds, the light will turn off.

**ALL NIGHT MODE KEY (3):** As long as the ambient brightness detected is less than about 40lux, the panel remains on at 10% light output until the battery is discharged or the sun rises.

**LOW LIGHT SENSOR MODE KEY (4):** In this mode the projector will turn, when motion is detected, at 100% output. If no motion is detected for 30 seconds, the projector will switch to 10% output until the next motion detected.

